

SAFETY DATA SHEET

Macka's Sand Products (VENM)

SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER				
Product Name:	Macka's Sand Products			
Other Names:	VENM Sand, Fill Sand			
Recommended Use:	Fill Sand is widely used in residential building, commercial			
	building, civil engineering and construction projects			
Application In:	Australia			
Supplier:	Macka's Sand Pty Ltd ABN 86 122 903 860			
Address:	2684 Nelson Bay road, Salt Ash NSW 2318, Australia			
Telephone:	+61 2 4982 6227			
Fax:	+61 2 4982 6506			
Website:	www.mackas.com.au			
Emergency Phone Number:	000 Fire Brigade and Police (available in Australia only)			
Poisons Information Centre:	13 11 26 (available in Australia only)			

This Safety Data Sheet (SDS) is issued by the Supplier in accordance with National standards and guidelines from Safe Work Australia (SWA – formerly ASCC/NOHSC). The information in it must not be altered, deleted or added to. The Supplier will not accept any responsibility for any changes made to its SDS by any other person or organization. The Supplier will issue a new SDS when there is a change in product specifications and/or Standards, Codes, Guidelines, or Regulations.

SECTION 2: HAZARD IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE: The products as supplied are **non-Hazardous** according to the criteria of Safe Work Australia (SWA – formerly ASCC/NOHSC) Approved Criteria for Classifying Hazardous Substances [NOHSC:1008] 3rd Edition.

Dust in/on the supplied product, or created when the product is processed, abraded, or crushed, is **Hazardous**. Dust of aggregate products contains crystalline silica, some of which may be respirable (particles small enough to go into the deep parts of the lung when breathed in). Recommendations on Exposure Controls / Personal Protection (see Section 8 below) should be followed.

Macka's Sand Products are classified as **Non-Dangerous** Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. GHS CLASSIFICATION:

Not classified as Hazardous. Because this product is classified as Non-Hazardous as delivered, a Safety Data Sheet (SDS) is not required under the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) or Australian Regulations. Macka's has elected to issue this SDS for the information of users, installers and the community. It has been formatted according to the GHS, as adopted by Safe Work Australia.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name:,	Synonyms:	Proportion:	CAS Number:
Fill Sand containing	VENM Sand	100%	14808-60-7
crystalline silica			
quartz)			

Notes:

Macka's Sand Products are mostly supplied from VENM naturally occurring materials excavated and processed at sand pits.

SECTION 4: FIRST AID MEASURES

The following advice refers mainly to exposure to dust coming from the product.

Swallowed:	Rinse mouth and lips with water. Do not induce vomiting. If
	symptoms persist, seek medical attention.
Eyes:	Flush thoroughly with flowing water for 15 minutes to remove all traces. Do not attempt to remove solid particles embedded in the
	eye. If symptoms such as irritation or redness persist, seek medical attention.
Skin:	Remove heavily contaminated clothing. Wash off skin thoroughly with water. Use a mild soap if available. Shower if necessary. Seek medical attention for persistent irritation or burning of the skin.
Inhaled:	Remove to fresh air, away from dusty area. If symptoms persist, seek medical attention
Advice to Doctor:	Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Suitable extinguishing	Use carbon dioxide, foam, dry chemical or water spray as
media:	required for fire in surrounding materials.
Specific hazards:	None
Special protective	None
equipment and	
precautions for	
firefighters:	
HAZCHEM Code:	None allocated

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions,	Recommendations on Exposure Controls / Personal Protection
protective equipment and	(see Section 8 below) should be followed during spill clean-up
emergency procedures:	if conditions are dusty.
Environmental	No specific precautions required.
precautions:	
Methods and materials for	Dust is best cleaned up by vacuum device to avoid making
containment and clean	dust airborne. Wetting down before sweeping up dust may be
up:	a useful control measure.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling:	Manual handling should be in accordance with Manual Handling Regulations and Codes. Avoid breathing dust. Respirable dusts can be generated during processing, handling, and storage.
Conditions for safe storage:	When stockpiling and handling large quantities of products, care should be taken to avoid having the faces of the stockpile steeper than the natural angle of repose of the material. Steep faces can fall without warning and trap persons resulting in injury and possibly suffocation.
Incompatibilities:	none

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Standards:	Workplace Exposure Standards for Airborne Contaminants, Safe Work Australia
	Crystalline silica (quartz): TWA – 0.1 mg/m³ respirable dust (□ 7 microns particle equivalent aerodynamic diameter)

	Total dust (of any type, or particle size): TWA -10 mg/m ³ Asbestos: TWA – 0.1 fibres/mL of air (fibrous actinolite is a form of asbestos)
Notes on Exposure	,
	All occupational exposures to atmospheric contaminants
Standards:	should be kept to as low as reasonably practicable and in all
	cases to below the Workplace Exposure Standard (WES).
	TWA (Time Weighted Average): the time-weighted average
	airborne concentration over an eight-hour working day, for a
	five-day working week over an entire working life. According to
	current knowledge this concentration should neither impair the
	health of, nor cause undue discomfort to, nearly all workers.
Biological Limit Values:	No biological limit allocated.
ENGINEERING CONTROLS	
_ 1/ /!! /!	
☐ Ventilation:	The products should be made damp before use to reduce dust
	generation. Work in the open air where possible. Local
	mechanical ventilation or extraction may be required in areas
	where dust could escape into the working environment. Local
	dust extraction and collection may be used, if necessary, to
	control airborne dust levels. If generated dust cannot be
	avoided, follow personal protection recommendations.
□ Special	Where possible vacuum or wash down all gear, equipment or
Consideration for Repair	mobile plant prior to maintenance and repair work. If
&/or Maintenance of	compressed air cleaning cannot be avoided, wear eye and
Contaminated Equipment:	respiratory protection, and clothing as listed below.
	Recommendations on Exposure Control and Personal
	Protection should be followed.
PERSONAL PROTECTION	Trotodich diledia se followed.
□ Personal Hygiene:	Wash hands before eating, drinking, using the toilet, or
- rersonarriygiene.	smoking. Wash work clothes regularly.
□ Skin Protection:	Wear loose comfortable clothing and gloves (standard duty
Skin Protection:	
□ Fye Duete-ti	leather or equivalent AS 2161).
☐ Eye Protection:	Safety glasses with side shields or safety goggles (AS/NZ
	1336) or a face shield should be worn.
Respiratory	None required if engineering and handling controls are
Protection:	adequate to minimize dust generation and dust exposure
	(e.g. products kept damp). Where engineering and handling
	controls are not enough to minimise exposure to dust,
	personal respiratory protection may be required.
	The type of respiratory protection required depends primarily
	on the concentration
	of the inhalable and respirable dust in the air, and the
	frequency and length of exposure time. A suitable P2
	particulate respirator chosen and used in accordance with
	AS/NZS 1715 and AS/NZS 1716 may be sufficient for many
	situations, but where high levels of dust are encountered, more
	efficient cartridge- type or powered respirators or supplied-air
Í	I halmata ar quita may be personary. Her only requireters that
	helmets or suits may be necessary. Use only respirators that

bear	the	Australian	Standards	mark	and	are	fitted	and
maint	aine	d correctly.						

Dust control measures providing respiratory protection against crystalline silica dust will also minimise and control any exposure to fibrous actinolite.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	The products are typically blue/grey in colour, but may also vary to brown, green, cream and white, depending upon source material. Shape and texture varies from smooth and rounded to angular and rough.
Odour:	None
Odour threshold:	Not applicable
pH:	Approximately 5.8
Melting point:	Not applicable
Initial boiling point and range:	Not applicable
Flash point:	Not applicable
Evaporation rate:	Not applicable
Flammability:	Non-flammable
Upper/lower flammability or explosive limits:	Not applicable
Vapour pressure:	Not applicable
Vapour density:	Not applicable
Specific gravity (Relative density):	2.1 – 3.2
Solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Viscosity:	Not applicable
Auto-ignition temperature:	Not applicable
Decomposition temperature:	Not determined

% Volatiles:	0%
Volatile Organic Compounds (VOC) Content:	0%
(as specified by the Green Building Council of Australia)	

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability:	Stable under normal conditions
Hazardous Reactions:	None
Conditions to avoid:	Dust generation
Incompatible Materials:	None
Hazardous Decomposition Products:	None

SECTION 11: TOXICOLOGICAL INFORMATION

Health Effects: Acute(short term)

Swallowed:	Unlikely under normal industrial use. Mildly abrasive to mouth and throat if swallowed.
Eyes:	Dust is irritating and may cause redness and watering. Exposure to dust may aggravate pre- existing eye conditions.
Skin:	Dust may be mildly irritating and drying to the skin, or abrasive, due to its physical characteristics.
Inhaled:	Dust is mildly irritating to the nose, throat and respiratory tract and may cause coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

Health Effects: Chronic (long term)

Eyes:	Dust may cause irritation and inflammation of the eyes and aggravate pre-existing eye conditions.
Skin:	Repeated heavy contact may cause drying of the skin and can result in skin rash (dermatitis) typically affecting the hands. Over time this may become chronic and can also become infected.

Inhaled:

Repeated exposure to the fine dust may result in increased nasal and respiratory secretions and coughing. Inflammation of lining tissue of the respiratory system may follow repeated exposure to high levels of dust with increased risk of bronchitis and pneumonia. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

Toxicity Data

No specific toxicology data available, but toxicity of this product is anticipated to be very low with LD50 >5,000mg/kg. Health effects information is based on reported effects in use from overseas and Australian

Effects:

Additional Notes	
Long Term Effects:	In some cases the aggregate in this product may contain traces of fibrous actinolite material, which is a form of asbestos (asbestiform fibres). Excessive long term exposures to asbestiform fibres can lead to mesothelioma, lung cancer and asbestosis. However, according to a statement from WA Government health authorities (14 November 2013):
	"Exposure monitoring results gathered during air monitoring programs at quarries and mine sites show that the levels of exposure from airborne mineral fibres are below the national occupational exposure standard and therefore present a low health risk."
	Long term occupational over-exposure or prolonged breathing-in (or inhalation) of crystalline silica dust at levels above the WES carries the risk of causing serious and irreversible lung disease, including bronchitis and silicosis (scarring of the lung). It may also increase the risk of other irreversible and serious disorders including scleroderma (a disease affecting the skin, joints, blood vessels and internal organs) and other auto-immune disorders. IARC have recently classified respirable crystalline silica dust as carcinogenic to humans (IARC Group 1). This means it may can cause lung cancer. In the case of generated dust, the recommended controls outlined in Section 8 should be followed.
	Following considerable research and consultation with Government authorities, Macka's considers low exposures to aggregate dust containing such traces are without risk to health.
Special Toxic	Inhalation of dust, including crystalline silica dust, is considered by medical authorities to increase the risk of lung disease due to

SECTION 12: ECOLOGICAL INFORMATION	
Eco-toxicity:	Products as delivered are not biodegradable, have low eco-toxicity and are not regarded as posing any ecological risk. Crushed products and dust may form mildly alkaline, mildly acidic or neutral slurry when mixed with water.
Persistence and Degradability:	Product is persistent and has a low degradability.
Bioaccumulative potential:	There is no evidence to suggest bioaccumulation will occur.
Mobility:	A low mobility would be expected in a landfill situation.

tobacco smoking.

SECTION 13: DISPOSAL CONSIDERATIONS

Macka's Sand Products can be treated as a common waste for disposal and can be dumped into a landfill site in accordance with local authority guidelines. Recycling into construction activities is usually a practicable alternative. Measures should be taken to prevent dust generation during disposal and exposure and personal precautions should be observed (see above).

SECTION 14: TRANSPORT INFORMATION

UN number:	None allocated
UN Proper Shipping Name:	None allocated
Class and Subsidiary Risk :	None allocated
Packaging Group:	None allocated
Marine Pollutant:	No
Special Precautions for User:	None
HAZCHEM code:	None allocated

SECTION 15: REGULATORY INFORMATION

Poisons Schedule:	Not scheduled
Poisons Schedule:	Not scheduled

Exposures by inhalation to high levels of dust may be regulated under the Hazardous Substances Regulations (State) as they are applicable to Respirable Crystalline Silica, requiring exposure assessment, controls and health surveillance.

SECTION 16: OTHER INFORMATION

Date of revision of this SDS: October 2019

Australian Standards References:

AS/NZS 1336	Recommended Practices for Occupational Eye Protection
AS/NZS 1715	Selection, Use and Maintenance of Respiratory Protective Devices
AS/NZS 1716	Respiratory Protective Devices

AS 2161	Industrial Safety Gloves and Mittens (excluding electrical and medical gloves)
---------	--

Other References:

NOHSC:1008 (2004)	Approved Criteria for Classifying Hazardous Substances
Model Code of Practice	Preparation of Safety Data Sheets for Hazardous Chemicals, December 2011, Safe Work Australia.
Model Code of Practice	Labelling of Workplace Hazardous Chemicals, December 2011, Safe Work Australia.
Model Code of Practice	Managing Risks Of Hazardous Chemicals In The Workplace, July 2012, Safe Work Australia.
WHS	Guidance on the Classification of Hazardous Chemicals under the WHS Regulations, April 2012, Safe Work Australia.
ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th edition, National Transport Commission.
WES	Workplace Exposure Standards For Airborne Contaminants, April 2013, Safe Work Australia.
WES	Guidance On The Interpretation Of Workplace Exposure Standards For Airborne Contaminants, April 2013, Safe Work Australia.
GHS	Globally Harmonized System of Classification and Labelling of Chemicals (GHS), 3rd revised edition, United Nations, New York and Geneva, 2009.
GHS	Understanding the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), United Nations, New York and Geneva, 2010.
HSIS	Hazardous Substances Information System (HSIS), internet advisory service, Safe Work Australia.
HCIL	GHS Hazardous Chemical Information List (HCIL), internet advisory service, Safe Work Australia.

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.

END OF SDS